



Proximity Keypad System

Standalone DG Series

DG-160/175/300/600/800/900



DG-160



DG-175



DG-300 Series



DG-600-E



DG-800



DG-900 Series









Standard Features

- Relay to control door lock and other security devices
- Backlit keypad for better visibility and operation (For DG-160, 175, 300, 800)
- Keypad tamper lockout
- Additional input for anti-tailgating to ensure higher security access control
- LED indicators and built-in buzzer for status and programming feedback
- Weatherproof (IP65)

Models	Voltage	Descriptions
DG-160	12~24 VDC	Slim/narrow size, 1000+10 PROX cards/tokens and 4 digit PIN codes, 2 Relays, 5 cm Read range, EM 125KHz
DG-175	12~24 VDC	Slim/narrow size, 1000 PROX cards/tokens and 4 digit PIN codes, 1 Electronic switch, 4 cm Read range, Piezo keypad, EM 125KHz
DG-300EM DG-300MF	12~24 VDC	ANSI size, 1000+10 PROX cards/tokens and 4 digit PIN codes, 2 Relays, EM 125KHz or Mifare 13.56MHz
DG-600-E	8.5~16 VDC	ANSI size, 600 PROX cards/tokens and 5 digit PIN codes, 2 Relays, 26-bit or 44-bit Wiegand, EM 125KHz
DG-800	12~24 VDC	Slim/narrow size, 1000+10 PROX cards/tokens and 4 digit PIN codes, 2 Relays, 5 cm Read range, EM 125KHz
DG-900-BA DG-900-WI	12VDC	ANSI size, 1000+10 PROX cards/tokens and 5 digit PIN codes, 2 Relays, 5~7 cm Read range, Mifare 13.56 MHz

Standalone DG Series Dimensions



All dimensions in mm