





Door Control Modules

Useful Gadgets

Item	Models	Descriptions
	ILM-200 Interlock Module	Input Voltage 12~24VDC Relay Rating: 3A@125VAC/30VDC Dimensions: 73(L) x 63(W) mm
	SM1228 Power Transformer Module	Input Voltage: 13~28 VDC Output Voltage: 300mA/12VDC Dimensions: 51(L) x 40(W) x15(D) mm
	DBR-200 Relay Board	Input Voltage: 8~30VDC/11~30VDC Current Draw: 45mA/12VDC Relay Rating: 5A/24VAC, 5A/30VDC
	FFP-1224-7A PSU Interface Module for Fire Alarm Panel (Supports Fail-safe or Fail-secure operation)	Input Voltage: 12~24VDC Output Voltage: 12~24VDC Relay Rating: 7A/30VDC
	PSM-S1A12V Weatherproof Voltage Switching Module	Input Voltage: 12~28VAC, 12~50 VDC Output Voltage: 1A/12VDC Efficiency: >70% Dimensions: 70(L) x 40(W) x 20(D) mm
	SM1224-1A Mini Voltage Switching Module	Input Voltage: 12~24VDC/AC Output Voltage: 300mA/12VDC Dimensions: 51(L) x 40(W) x 15(D) mm
	SM1224-1A-N Full Wave Bridge Rectifier with LED Indicator	Converts AC to unfiltered DC Input Voltage: 12~24VDC/AC Output Voltage: 1A/12VDC Dimensions: 58.5(L) x 23.5(W) x 22(D) mm