



HIGH SECURITY RFID CARD READER TOUCH SCREEN / KEYPAD + BIOMETRICS



COMPATIBILITY

- MIFARE® Classic & Classic EV1
- MIFARE Plus®
- MIFARE® DESFire® 256, EV1 / EV2
- SECard software
- OSDP™ / SSCP protocols



LET YOUR IMAGINATION FLOW

Customization
of the multicolor LEDs
(RGB, 360 colors)



Your logo, customized
image and text display



CERTIFICATIONS



SMART FUNCTIONS



« **Scramble Pad** »: protects your access control system from unauthorised use of access codes by randomly displaying keys.



Hybrid: display of information (logo, instructions, personalized messages, images) and keyboard by a simple touch-screen wake-up call.



Bell: Touch button allowing you to use the reader as a standard bell.

ADVANCED ANTI-FRAUD FUNCTIONS

The Architect® biometric reader is designed to resist fraud attempts:

- **False finger detection**: the reader detects a wide range of counterfeit fingerprints made of latex, Kapton, transparent film, rubber, graphite, etc.
- **Detection of live fingers**
- **Duress finger**: the admin can assign a finger number dedicated to authentication when the user is threatened.

SECURE YOUR CRITICAL SITES WITH A STRONG AUTHENTICATION

The Architect® ARC-F reader provides secure multi-factor authentication by combining the most secure open RFID technologies on the market, a touch screen / keypad and a biometric fingerprint sensor.

FINGERPRINT SECURE MANAGEMENT

Several fingerprint management possibilities depending on your security needs:

- **Fingerprint templates directly stored in the RFID card** (CNIL French legislation compliance).
- **Fingerprint templates stored in the reader or in the system.**
- **Biometric derogation** to manage one-time visitor or difficult finger etc.

WELCOME TO HIGH SECURITY

The reader uses the latest MIFARE® DESFire® EV2 contactless chip technologies with new data security mechanisms:

- **Secure Messaging EV2**: secure transaction method based on AES-128 with protection against interleaving and replay attacks.
- **Proximity Check**: improved protection against relay attacks.

All public encryption algorithms can be used (3DES, AES, RSA, SHA, etc.), which are recommended by official data security agencies (such as the French national agency ANSSI).



SPECIFICATIONS

Operating frequency/Standards	13.56 MHz. ISO14443 type A
Chip compatibility	MIFARE® Classic & Classic EV1, MIFARE Plus® & Plus® EV1, MIFARE® DESFire® 256, EV1 & EV2
Functions	Read only: private ID (sector/file) or Secure Protocol (Secure Plus) / Secure Read Write
Digital fingerprint sensor	Optical (SAFRAN MorphoSmart™ CBM E3) - ≤ 1 second for a 1:1 authentication
Communication interfaces & protocols	TTL Data Clock (ISO2) or Wiegand (ciphered mode - S31) / RS232 (ciphered mode S32) / RS485 (ciphered mode - S33) with secure communication protocols SSCP & SSCP2 ; OSDP™ V1 (plain communication) & V2 (SCP secure communication)
Decoder compatibility	Compatible with EasySecure interface
Touch Screen	Color touch screen - 2.8" - 240 x 320 pixels / 12 keys - Standard or Scramble pad mode Functions: Card AND Key / Card OR Key Configuration by RFID card, software or UHF technology according to the interface
Reading distances*	Up to 4 cm / 1.57" with a MIFARE DESFire® EV2 or Classic card
Light indicator	2 LEDs RGB - 360 colors Configuration by RFID card, software, external command (0V) or UHF technology according to the interface
Audio indicator	Internal buzzer Configuration by RFID card, software, external command (0V) or UHF technology according to the interface
Power requirement	Typical 350 mA / 12 VDC
Power supply	7 VDC to 28 VDC
Connections	10-pin plug-in connector (5 mm / 0.2") / 2-pin plug-in connector (5 mm / 0.2"): O/C contact - Tamper detection signal or the reading of a credential
Material	ABS-PC UL-V0 (black) / ASA-PC-UL-V0 UV (white)
Dimensions (h x w x d)	166.2x 80 x 30.2/71 mm / 6.54" x 3.15" x 1.19/2.8" (general tolerance following ISO NFT 58-000 standard)
Operating temperatures	- 10°C to + 50°C / De + 14°F a + 122°F / Humidity: 0 - 95%
Tamper switch	Accelerometer-based tamper detection system with key deletion option (patented solution)
Protection	IP65 Level - Weather-resistant with waterproof electronics (CEI NF EN 61086 certification)
Mounting	Compatible with any surfaces and metal walls - Wall mount / Flush mount: - European 60 & 62 mm / 2.36" & 2.44" - American (metal/plastic) - 83.3 mm / 3.27" - External dimensions: 101.6 x 53.8 x 57.15 mm / 3.98" x 2.09" x 2.24" Examples: Hubbel-Raco 674, Carlon B120A-UP
Certifications	CE, FCC and UL
Part numbers	
Read only	Secure - TTL ARC-R31-F/PH5-xx/y Secure / Secure Plus - TTL ARC-S31-F/PH5-xx/y Secure - RS232 ARC-R32-F/PH5-5AB/y Secure - RS485 ARC-R33-F/PH5-7AB/y Secure / EasySecure Interface - RS485 ARC-R33-F/PH5-7AA/y Secure / Secure Plus - RS485 ARC-S33-F/PH5-7AB/y Secure / Secure Plus / EasySecure Interface - RS485 ARC-S33-F/PH5-7AA/y
Read/write	Secure - RS232 ARC-W32-F/PH5-5AA/y Secure - RS485 ARC-W33-F/PH5-7AA/y Secure SCP2 CSPN compliant - RS485 ARC-W33-F/PH5-7AD/y Secure OSDP™ - RS485 ARC-W33-F/PH5-7OS/y


y: casing color (1: black - 2: white)

DISCOVER OUR CREDENTIALS



13.56 MHz ISO cards
& key holders

AND OUR ACCESSORIES



Decorative plate / Spacers / Mounting plate /
Privacy filter...



SECARD
SECard configuration kit and SSCP,
SSCP2 & OSDP™ protocols

*Caution: information about the distance of communication: measured from the centre of the antenna, depending on the type of identifier, size of the identifier, operating environment of the reader, power supply voltage and reading functions (secure reading).
Legal statements: STid, STid Mobile ID® and Architect® are trademarks of STid SAS. All other trademarks are property of their respective owners. This document is the exclusive property of STid. STid reserves the right to stop any product or service for any reason and without any liability - Noncontractual photographs.

Headquarters / EMEA

13850 Gréasque, France
Tel.: +33 (0)4 42 12 60 60

PARIS-IDF Office

92290 Châtenay-Malabry, France
Tel.: +33 (0)1 43 50 11 43

STid UK Ltd. LONDON

Hayes UB11 1FW, UK
Tel.: +44 (0) 192 621 7884

STid UK Ltd.

Gallows Hill, Warwick CV34 6UW, UK
Tel.: +44 (0) 192 621 7884

NORTH AMERICA Office

Irving, Texas 75063, USA
Tel.: +1 310 803 2114

LATINO AMERICA Office

Cuahtémoc 06600 CDMX, México
Tel.: +521 (55) 5256 4706

AUSTRALIA / APAC Office

Ultimo, Sydney NSW 2007, Australia
Tel.: +61 (0)2 9274 8853

info@stid.com

www.stid-security.com