

The mechatronic access control solution for data center racks.

- Ideal for (de)centralized data center environments
- Integrates into existing management system
- Emergency power interface for battery pack
- Gapless audit trail
- One and two factor authentication



	MLR5000 KP	MLR3000 KP	MLR5000	MLR3000	MLR1000	
Interface	Ethernet	RS 485	Ethernet	RS 485	—	
Storage space transponder		1,000		2,000	—	
Storage space PIN		1,000		—	—	
Stand-alone		possible		possible	—	
LED handle status	■	—	■	—	■	
Keypad with LED keypad status	■	—	—	—	—	
LED temperature status	■	—	■	—	—	
LED sabotage alarm/ready for opening	■	—	■	—	—	
Illuminated info field	—	—	Color configurable	—	Color configurable	
Door contact input	■	—	■	—	—	
Storage for 500 events and 30 time profiles	■	—	■	—	—	
Integrated real-time clock	■	—	■	—	—	
Power supply ±10%(DC)/standby current (DC)/max. current consumption (DC)	12V/45mA/440mA	—	12V/40mA/440mA	—	12V/40mA/410mA	
Reader 125 kHz	■	—	■	—	—	
Reader 13.56 MHz	■	—	■	—	—	
Conditional Relay	■	—	■	—	—	
Relay output	—	—	—	—	—	
Power over Ethernet capable	■	—	■	—	—	